

HORIZON® COATING

Full wall, footer to sill plate moisture protection

Product Overview

The Horizon® Coating System works with your Tremco below-grade foundation waterproofing system to provide footing-to-sill plate moisture protection, while improving the appearance of your exposed above-grade foundation wall.

Features & Benefits

Two-Part Barrier System

- Your Tremco below-grade exterior waterproofing system protects your foundation from leaks and seepage, and if insulated, interior condensation.
- The Horizon Coating System continues your waterproofing protection from the grade line to the sill plate, and beautifies the exterior of your poured or block foundation wall.

Protection from Footing to Sill

- The Horizon Coating System starts with proven below-grade foundation waterproofing protection offered by Tremco.
- The Horizon Coating System is completed with your choice of highly-durable Horizon Coarse Coat or Horizon Matte Coat from the grade-line to the sill plate. Horizon Coarse Coat provides a more textured finished look, while Horizon Matte Coat offers a smoother clean-looking finish to your exterior above-grade walls. With either UV-resistant finish coat, the Horizon Coating System meets the below-grade waterproofing system at the grade line, completing the full-wall waterproofing protection and eliminating the troubleshooting grade-line spot at which the majority of wall leaks occur.

From Tremco, Offering Barrier Solutions

Horizon Foundation Finishing Systems come from Tremco, with a heritage in spray-applied barrier technology stretching back more than 30 years. Since 1983, our team has sparked innovations in fluid membrane formulations and performance. And we offer more than three decades of experience installing spray-applied barriers - including the TUFF-N-DRI® Basement Waterproofing System, the #1 brand of new basement waterproofing in North America.



Horizon Coarse Coat (shown in photo above) provides a durable, textured topcoat that repels moisture and gives exposed foundations an attractive, finished look.

Installed by Trained Professionals

Horizon Foundation Finishing Systems are reliably installed by Select Barrier Solutions Contractors. Count on our quality-trained contractors to professionally and promptly install Horizon Foundation Finishing Systems on the homes you build.

MEMBRANE PROPERTIES		
Type	Elastomeric, emulsion based coating	
Color	Grey	
Application Temperature	32°F (0°C) to 100°F (38°C)	
Cure Time	24 Hours	
Film Thickness	40 mils dry at 25ft ² /gal.	
Elongation	150%	Method: ASTM D2370
Mandrel Bend	1/2" at -15°F (-26°C)	Method: ASTM C711
Water Vapor Permeance	6 perms	Method: ASTM E96
MATTE FINISH		COARSE FINISH
Solids	63 ± 2 [percent by weight]	72 ± 2 [percent by weight]
Density	8.2 ± .4 lb/gal.	10.0 ± .5 lb/gal.
Application	Airless Spray/Brush	Air Atomized Texture Spray/Brush

For more information, contact Tremco at **800-876-5624**.

For more details about the Horizon Foundation Finishing Systems, call your local Tremco Contractor.